

Floor Network Cabinet



Degree of Protection

IP20

Surface Finish:

Degreasing, picking, phosphating, Powder Coated

Standard:

Comply with ANS/EIA RS-310-D, IEC 297-2, DIN41497 Part 1, DIN41494 Part 7, ETSI.

Features:

- Exquisite design with precise craftsmanship;
- Welded steel frame of front and back part, flat packing is easy for loading and transportation;
- Tempered glass of front door with over 180 turning degree, vented front door border;
- Steel reel door with little round lock, other type of lock is optional;
- Adjustable feet and castors;
- Cable entry on the top, adjustable cable entrance at the bottom with panel;
- Advanced handle locks for front door, other types of locks are optional;
- Efficient baying kit, earthing kit;
- Various optional accessories for installation;
- Flat assembled packing saves big space of container.

Material:

- SPCC quality cold rolled steel;
- Thickness: 2.0mm - 1.5mm - 1.2mm.

Loading Capacity

Static loading: 800kgs

For More Information:

Email: sales@telex.cn

www.telex.cn

Capacity (U)	Width*Depth (mm)	Fan	PDU	Shelf	Capacity (U)	Width*Depth (mm)	Fan	PDU	Shelf
18	600*600	2	1	1	18	800*600	2	1	1
	600*800	4	1	1		800*800	4	1	1
	600*900	4	1	1		800*900	4	1	1
	600*1000	4	1	1		800*1000	4	1	1
22	600*600	2	1	1	22	800*600	2	1	1
	600*800	4	1	1		800*800	4	1	1
	600*900	4	1	1		800*900	4	1	1
	600*1000	4	1	1		800*1000	4	1	1
27	600*600	2	1	1	27	800*600	2	1	1
	600*800	4	1	1		800*800	4	1	1
	600*900	4	1	1		800*900	4	1	1
	600*1000	4	1	1		800*1000	4	1	1
32	600*600	2	1	2	32	800*600	2	1	2
	600*800	4	1	2		800*800	4	1	2
	600*900	4	1	2		800*900	4	1	2
	600*1000	4	1	2		800*1000	4	1	2
37	600*600	2	1	2	37	800*600	2	1	2
	600*800	4	1	2		800*800	4	1	2
	600*900	4	1	2		800*900	4	1	2
	600*1000	4	1	2		800*1000	4	1	2
42	600*600	2	1	3	42	800*600	2	1	3
	600*800	4	1	3		800*800	4	1	3
	600*900	4	1	3		800*900	4	1	3
	600*1000	4	1	3		800*1000	4	1	3
45	600*600	2	1	3	45	800*600	2	1	3
	600*800	4	1	3		800*800	4	1	3
	600*900	4	1	3		800*900	4	1	3
	600*1000	4	1	3		800*1000	4	1	3
47	600*600	2	1	3	47	800*600	2	1	3
	600*800	4	1	3		800*800	4	1	3
	600*900	4	1	3		800*900	4	1	3
	600*1000	4	1	3		800*1000	4	1	3