

2U 19" UTP Cat. 5E/ Cat. 6/ Cat. 6A Patch Panel – 48 Ports



Electrical:

- Voltage rating: 125 VAC RMS;
- Current rating: 1.5 AMP;
- Contact resistance: 20 Million HMS max. ;
- Insulation resistance: 100 MEGOHMS min. @ 500 VDC;
- Dielectric strength: 750 VAC RMS 60 Hz, 1 min. ;
- C6 permanent link: conform to AN-SI/TIA/EIA-568 b.2-1.

Mechanical:

- Housing Material: PBT+15% GF;
- Panel frame: ST-12, powder coating in black color;
- IDC material: PC, Contact: phosphor bronze, Tin plated;
- RJ 45 Jack life: 750 cycles min.;
- IDC life: 200 times min. ;
- Wire: AWG 22-24;
- TIA Cat. 5E fluke perm link test: worst pair next margin ≥ 8 dB;
- TIA Cat. 6 fluke perm link test: worst pair next margin ≥ 6 dB;
- TIA Cat. 6A fluke perm link test: worst pair next margin ≥ 5 dB;
- Retentiveness of insertion structure: 50N 60 \pm 5 S.

Environment of Adaptations:

- Storage: - 40 °~ 70 °
- Operation: -10 °~ 60 °

For More Information:

Email: sales@telexmax.cn

www.telexmax.cn