



MARK	ECN NO.	DATE	DRAW	APPROVE

**FEATURES:**

**1 Electrical Test:**

- A. Safety Voltage/Current Rating 150V ac, at 1.5A.
- B. Dielectric with standing 1000V/DC/min, <0.5A.
- C. Insulation Resistance:>500M Ω, 1000V./min
- D. Contact Resistance:<20M Ω

**2 Mechanical:**

- A. Cable-to-Plug tensile strength-20LBs(89N)min.
- B. Durability:750 mating cycles.

**3 Operation Temperature:-40℃~+85℃.**

**4. Environmental compliance**

- A. the products are compliant with the RoHS, and REACH ETC.

**5. Safety standards:UL E239590**

**特征:**

**1 电气特性:**

- A. 额定电压150伏特AC. 额定电流1.5A
- B. 耐电压测试: 小于0.5安培1000伏特DC/一分钟.
- C. 绝缘抗降: 1000伏特DC/一分钟, 大于500百萬歐姆
- D. 接觸除坑: 不大于20m Ω (毫歐姆)

**2 機械特性:**

- A. 拉力测试-電纜至插座張力強度至少一分钟20磅 (89N)
- B. 耐久测试-拔插测试750次以上.

**3 使用温度范围: -40℃~+85℃**

**4 环保符合性:**

- A. 产品符合RoHS, REACH等环保规格.

**5 安全标准: UL E239590**

注: 带▲为重点尺寸控制

TELEMAX® SHENZHEN TELEMAX TECHNOLOGY CO.,LTD

BLADE:	A5	B4	B7	B9	B20	A3	B7	<input type="checkbox"/> 屏蔽壳 Shield	<input type="checkbox"/> 黄铜 Brass	<input type="checkbox"/> 铁 Steel	1
Drawing								Au: <input type="checkbox"/> G/F" <input type="checkbox"/> 1u" <input type="checkbox"/> 3u" <input type="checkbox"/> Ni <input type="checkbox"/> 80u"			
Mark								胶壳 PC(聚碳酸酯) <input type="checkbox"/> 94-V0 <input checked="" type="checkbox"/> 94-V2			1
BLADE:	A4	A10	B6	B10	金片 (PIN针) Contacts		<input checked="" type="checkbox"/> 黄铜 Brass	<input type="checkbox"/> 磷铜 Phosphor copper			8
Drawing					<input type="checkbox"/> G/F" <input type="checkbox"/> 1u" <input type="checkbox"/> 3u" <input type="checkbox"/> 6u"	<input type="checkbox"/> 15u" <input type="checkbox"/> 30u" <input type="checkbox"/> 50u" <input type="checkbox"/> OTHER					
Mark											

品名规格 DESCRIPTION					页次 SHEET	1/1
产品编号 PRODUCT NO	单位 UNIT	mm	比例 SCALE	1:1	版本 EDITI	A/0
DIMENSION IN mm(Inch) TOLERANCE UNLESS OTHERWISE SPECIFIED	第三视角法 THIRD ANGLE PROJECTION		制图 DRAW	廖庆环	日期 DATE	2018. 10. 07
x, x ±0.2			核对 CHECK	柯2	日期 DATE	2018. 10. 07
x, xx ±0.10			批准 APPRO	柯悦	日期 DATE	2018. 10. 07
x, xxx ±0.050						