

## Legrand Cat 6 UTP Keystone Jack Rotary Type



### Standard:

ISO/IEC 11801,ANSI/TIA/EIA-568-B

### Electrical:

- Voltage rating: 125 VAC RMS;
- Current rating: 1.5 AMP;
- Contact resistance: 20 Million HMS max;
- Insulation resistance: 100 MEGOHMS min. @ 500 VDC;
- Dielectric strength: 750 VAC RMS 60 Hz, 1 min.;

### Mechanical:

- Housing Material: PC
- INSERT MATERIAL: Flame retardant PC110
- PCB MATERIAL:FR-4 T=1.6 MM
- Contact MATERIAL: phosphor bronze stamp pin T=0.35MM
- IDC Material: phosphor bronze T=0.5mm with Plating
- RJ 45 Jack life: 750 cycles min.;
- IDC life: 200 times min.;
- Dual IDC
- Wire: AWG 22-26
- TIA Cat. 6 perm Link test: worst pair next margin  $\geq 7$ dB
- Retentiveness of insertion structure: 50N 60 $\pm$ 5 S.

### Environment of Adaptations:

- Storage: -40° ~ 70°
- Operation: -10° ~ 60°

### For More Information:

Email: [sales@telex.cn](mailto:sales@telex.cn)

[www.telex.cn](http://www.telex.cn)