


- ① All cable 100% testing, any open, miswiring, short & intermittent are not permitted.
全部导通测试, 无短路、断路现象。
- ② After crimping the distance between the bottom of contact and the top surface of plug are 5.90~6.146mm.
小金钢压着晶片后高度 5.90~6.146mm.
- ③ RoHS compliant PVC or PE or LSZH Jacket
符合RoHS 标准的PVC、PE或低烟无卤外套
- ④ Installation temperature $^{\circ}\text{C}$ -20 $^{\circ}\text{C}$ ~+75 $^{\circ}\text{C}$; Minimum bending Radius: 8D
安装温度 -20 $^{\circ}\text{C}$ ~+75 $^{\circ}\text{C}$; 最小折弯半径: 8D

③	注塑护套 Boots		48P PVC			
②	线材 Cable	1 PCS	外被 Jacket	PVC ☐ PVC-CM ☐ LSZH ☐		
			CAT 6A S/FTP 30AWG (7/0.10)*4P Stranded Cable OD:4.7±0.3mm. Braid:Aluminum Magnesium Alloy wire≥0%			
①	水晶头 Modular Plug	2 PCS	股料 Housing	94V-2 ☐ 94V-0 ☐	黄铜屏蔽壳 Brass Shell	Ni:80u" ☐ Au ☐
			金片 Contacts	G/F" ☐ 1u" ☐ 3u" ☐ 15u" ☐ 30u" ☐ 50u" ☐	黄铜 Brass ☐	磷铜 Phosphor copper ☐
NO.	ITEM	QTY	DESCRIPTION			

Telex Technology Co., Ltd

产品编号 PRODUCT NO		品名规格 DESCRIPTION	CAT. 6A S/FTP PATCH CORD			图号 DWG NO	6ASF10ALM95
尺寸公差表 DIMENSIONAL TOLERANCE (针对 CHANNE线线) 1000 ±15MM 2000 ±20MM 3000 ±30MM 5000 ±50MM		单位 UNIT	mm	比例 SCALE	1:1	版本 EDITI	A/0
		第三视角法 THIRD ANGLE PROJECTION 		制图 DRAWN	Chen Zhe	日期 DATE	2023. 12. 21
				核对 CHECK		日期 DATE	
				批准 APPROVAL		日期 DATE	

单体测试 Patch Cord Test